

TITAN-C



		Sin resistencia FH0C7FD*M*/TCWM2013*** / CWT29M**R*	Con resistencia FH0C7FD*MS/CWT29M**H*
CILINDRO			
Volumen del tambor	cu.ft (ℓ)	5.2 (147)	5.2 (147)
Diámetro	in. (mm)	24 (610.8)	24 (610.8)
Profundidad	in. (mm)	20.4 (518.1)	20.4 (518.1)
DIMENSIONES			
ProductO (WxHxD)	in	29 x 40.8 x 32	29 x 40.8 x 32
	mm	737 x 1,036 x 814	737 x 1,036 x 814
Con la puerta abierta	in. (mm)	53 (1,370)	53 (1,370)
	in	31 x 44.3 x 33.3	31 x 44.3 x 33.3
Ebalaje (WxHxD)	mm	788 x 1,125x 846	788 x 1,125x 846
Peso (Product/Cartron)	lb (kg)	221.8 (100.6) / 248 (112.5)	221.8 (100.6) / 248 (112.5)
VELOCIDAD⁽⁹⁾			
Lavar	RPM	46	46
Extracto (Alta velocidad)	RPM	1,000	1,000
Fuerza G	G	342	342
CLASIFICACIÓN⁽⁷⁾			
Clasificaciones eléctricas	V/Hz/A	100~120 / 50 or 60 / 4.2~5 (Heating 8.5~9.0) ⁽¹⁾ 220~240 / 50 or 60 / 2.1~2.3 (Heating 9.1~10) ⁽¹⁾	- 220~240 / 50 or 60 / 13.3~17.5
*ÍNDICE DE CONSUMO⁽²⁾			
Agua	gal (ℓ)	16.5 (62.5)	12.4 (47)
Electricidad	V/kW	100~120 / 0.5(Heating 0.85~1.0) ⁽¹⁾ 220~240 / 0.5(Heating 2.0~2.4) ⁽¹⁾	220~240 / 3.2~3.8
RUÍDO & DURACIÓN DE CICLO			
Nivel de ruido (Potencia sonora)	dB	Menor de 60	Menor de 60
Duración del programa en minutos (Default) ⁽¹⁾	min	36	59
SISTEMA & CONTROL			
Inverter Direct Drive Motor		O	O
Elemento de calefacción	V/W	100~120 / 1,000 ⁽¹⁾ 220~240 / 2,000 ⁽¹⁾	- 220~240 / 3200
Sistema de drenaje		BLDC	BLDC
Botón de parada de emergencia		O (OPL Only)	O (OPL Only)
Interfaz de dosificación automática		O	O
Amortiguador		O	O
Tambor		4 Friction Dampers	4 Friction Dampers
PROGRAMS⁽⁹⁾			
Lista de programas		Hot*	90°C
		Warm*	75°C
		Cold*	60°C
		Delicates*	40°C/30°C
		Add Super Wash (Card & Coin)/ 20 Custom PGM (OPL)	Cold * Custom PGM ⁽³⁾
ACABADO EXTERNO			
Tambor		Acero Inoxidable	Acero Inoxidable
PROTECCIÓN DEL CIRCUITO			
Fusible PCB-Panel de Control Principal	amps	12 (220~240V)	12 (220~240V)
Fusible PCB-Embalaje de Filtro	amps	15	15