LIGHT TITAN-C DRYER SPECIFICATIONS

		Gas CDT29M**** / R*1840***	Elec CDT29M**** / RV1840***
CYLINDER			
Drum Volume	cu.ft (ℓ)	9.0 (254)	9.0 (254)
Diameter	in. (mm)	28.2 (716)	28.2 (716)
Depth	in. (mm)	24.2 (614)	24.2 (614)
DIMENSIONS			
Product (WxHxD)	in	29 x 40.2 x 31.9	29 x 40.2 x 31.9
	mm	737 x 1,022 x 810	737 x 1,022 x 810
With Door Open	in. (mm)	53.2 (1,350)	53.2 (1,350)
Carton (WxHxD)	in	31.5 x 45.6 x33.8	31.5 x 45.6 x33.8
	mm	800 x 1158 x 858	800 x 1158 x 858
Weight (Product/Carton)	lb (kg)	150 (68.2) / 167.1 (75.8)	150 (68.2) / 167.1 (75.8)
RATING[o)]			
		220~240/50/2.4	220~240/50/22.5
***CONSUMPTION INDEX PER CYCLE[o)]**			
Electricity	kW	0.35 (Max 0.7)	5,4
SYSTEM & CONTROL			
Heating Type		Gas (LNG/LPG)[1)]	Electric
Type of Drying		Ventilation	Ventilation
Air Flow	CFM	210	210
Gas Ratings[o)]	kW/BTU	7.4 / 25,000	-
Motor	kW	0,33	0,33
Program Duratin in Minutes (Default)[o)]	min	40	45
CONNECTIONS			
Air Outlet Diameter	in. (mm)	4 (100)	4 (100)
Exhaust Airflow Diameter	in. (mm)	4 (100)	4 (100)
PROGRAMS			
Program List		High Temp	High Temp
		Med Temp	Med Temp
		Low Temp	Low Temp
		Extra Dry	Extra Dry
EXTERNAL FINISH			
Drum		Stainless Steel	Stainless Steel

*Dimensions and weights are approximate. *Design, features, and specifications subject to change without notic
*Some models may not be available for sale in certain countries. *Model name may vary by country
0) This specification is different by countries. For the most accurate information, please refer to service manual.
1) Gas type depends on country sales model.

e.